1/1 - (C) FILE CAPLUS

AN - 1999:531112 CAPLUS

DN - 131:158334

TI - Aqueous dispersion vinylamine polymer and its manufacture

IN - Nishimura, Akiko; Kubo, Katsuhisa; Ueno, Chie

PA - Kurita Water Industries, Ltd., Japan; Mitsubishi Chemical Industries Ltd

SO - Jpn. Kokai Tokkyo Koho, 8 pp.

CODEN: JKXXAF

DT - Patent

LA - Japanese

IC - ICM C08J003/03

ICS C08J003/075; C08F8/12; C08F26/02; C08K3/16; C08K3/28;

C08L039-00; C08L039-06

CC - 37-3 (Plastics Manufacture and Processing)

FAN.CNT 1

PATENT NO. KIND DATE APPLICATION NO. DATE

PN - JP11228704 / A 19990824 JP 1998-37694 19980219 <--

- The dispersion, having relatively low viscosity at a high concn., comprises an aq. polymer having vinylpyrrolidone unit, optionally, a polymer having N-vinylcarboxylic acid amide (I) unit and I and/or a copolymer of I and other monomers, and an inorg. salt. Thus, polymn. of N-vinylformamide 171, acrylonitrile 127 and vinylpyrrolidone-vinyl aceta copolymer 65 g in the presence of 2,2'-azobis(amidinopropane) dihydrochloride, adding 35% aq. HCl and MeOH and hydrolization in the presence of NaNO3 gave an aq. dispersion having particle size 4-20 .mu.m

- vinylformamide acrylonitrile copolymer aq dispersion; vinylpyrrolidone

vinyl acetate copolymer hydrolization dispersion

IT - Dispersion (of materials)

(aq. dispersion vinylamine polymer and its manuf.)

IT - Polyoxyalkylenes, uses

RL: MOA (Modifier or additive use); USES (Uses)

(aq. dispersion vinylamine polymer and its manuf.)

IT - Polymerization

(dispersion; aq. dispersion vinylamine polymer and its manuf.)

RL: IMF (Industrial manufacture); PRP (Properties); PREP (Preparation)

(ag. dispersion vinylamine polymer and its manuf.)

TT - 7631-99-4, Sodium nitrate, uses 7647-14-5, Sodium chloride, uses 9002-89-5, Polyvinyl alcohol 9003-39-8, Polyvinylpyrrolidone 25086-89-9, Vinyl acetate-vinylpyrrolidone copolymer 25322-68-3, Polyethylene glycol

RL: MOA (Modifier or additive use); USES (Uses)

(aq. dispersion vinylamine polymer and its manuf.)